

EvBlack XEV72

特种炭黑 Special carbon black

简介 introduction:

特种炭黑 EvBlack XEV72 设计用于导电塑胶、导电涂料、无线电元件、导电橡胶及其他防静电领域等，粒径小、比表面积大且表面粗糙、表面洁净。Special carbon black EvBlack XEV72 is designed for conductive plastics, conductive coatings, radio components, conductive rubber and other anti-static fields, etc., with small particle size, large specific surface area and rough surface and clean surface.

理化性质 Physical and Chemical Properties	参数 parameter
外观 Appearance	细砂粒 Fine Sand
平均原生粒径 Average primary particle size (nm)	30±1
BET 比表面积 BET Specific surface area (m ² /g)	250±10
DBP 吸油值 DBP Oil Absorption (cc/100g)	190±5
相对着色, Tinting strength IRB#3(%)	85±5
挥发份 Volatile matter (%)	0.2+1
密度 Density(g/L)	250±5

应用与特性 Application and characteristics:

- ◆ 粒径小 Small particle size
- ◆ 结构高 High structure
- ◆ 高纯度 High purity

推荐应用 Recommended application:

用于导电塑胶、导电涂料、无线电元件、导电橡胶及其他防静电领域

For conductive plastics, conductive coatings, radio components, conductive rubber and other anti-static fields.

包装 packing: 15KG/Bag

备注: 本数据资料的提供出于诚意, 仅供参考, 需要由您自己测试并决定是否适合您的用途, 对我们产品的应用和处理以及您制造的最终产品都处于我们的控制之外, 我们无法承担保证和义务。

PS: The Data above is provided in good faith, FYI.

工厂地址: 新疆胡杨河市胡杨经济技术开发区车排子西路 3 号

公司地址: 东莞市常平镇桥沥南北路 25 号

电话: +86 (0) 755 23246611; 13510821649

传真: +86 (0) 755 29467129

邮箱: texong@163.com 网址: www.texong.com